

Get ENERGY STAR® efficiency, optimal ventilation capacity and great lighting—all in one integrated unit

# P195ES

## ENERGY STAR®

### rated power pack

HVI certified performance

ENERGY STAR® rated hood for ducted applications provides optimum energy savings

Heat Sentry™ detects excessive heat and adjusts speed to high automatically

Charcoal filter option available for recirculation applications (Please note: Recirculation installations will not meet ENERGY STAR® requirements)

Optional liners protect cabinets and create a beautiful finish. Shown with a custom-fabricated liner purchased locally



#### Hood Sizes

**Width** 20-1/2": P195ES52SB  
27-1/2": P195ES70SB

**Depth** 11-1/4"

#### Finish

|               |                                        |
|---------------|----------------------------------------|
| Stocked       | Brushed Standard Grade Stainless Steel |
| Special Order | Not Available                          |

#### Features

|                         |                                |
|-------------------------|--------------------------------|
| Light Type              | Fluorescent Bulbs 13 W, G24Q-1 |
| Number of Lamps         | 2                              |
| Lighting Levels         | 1                              |
| Lighting Lamps Included | Yes                            |
| Control Type            | 3-Speed slider switch          |
| Control Features        | Heat Sentry™                   |
| Control Remote          | No                             |
| Filter: Standard        | Aluminum Mesh Filter           |
| Filter: Options         | Not Available                  |
| Non-ducted Capability   | Yes                            |

#### Blower (Included)

|                                           |                                              |
|-------------------------------------------|----------------------------------------------|
| Energy star rated internal CFM (High/Low) | 290/120 (P195ES52SB)<br>370/120 (P195ES70SB) |
| Sones Max Hi/Lo                           | 5.0/0.5 (P195ES52SB)<br>5.0/0.3 (P195ES70SB) |







#### Accessories

|                                        |                                                                          |
|----------------------------------------|--------------------------------------------------------------------------|
| Recirculation Filter                   | FILTEREB40 (for P195ES52SB)<br>ROUNDFILTER (for P195ES70SB)              |
| Liners: Optional                       | L5230 (for P195ES52SB)<br>L7030 / L7036 / L7048 (for P195ES70SB)         |
| Universal Make-up Air Damper: Optional | MD6TU for 6" duct (for P195ES70SB)<br>MD8TU for 8" duct (for P195ES70SB) |

#### Installation Requirements

|                            |                                          |
|----------------------------|------------------------------------------|
| Amps @ 120V                | 2.8 Amps                                 |
| Electrical                 | Cord Connected                           |
| Duct Size: Internal Blower | 6" Round (290 CFM)<br>8" Round (390 CFM) |
| Duct Size: External Blower | Not Available                            |
| Duct Direction             | Vertical                                 |
| Backdraft Damper           | Included                                 |



A. Installation height above the cooking surface 24–30"

B. Distance from bottom of range hood to top of hood 9-5/8"



Two fluorescent lights provide bright cooktop lighting.



Variable 3-speed slider switch control enables the user to choose operating preference.



Protect cabinetry from steam and grease with stainless steel liners that provide a custom fit.

