

ASHLYN™ BATH COLLECTION



With sleek angular lines and soft edges, the Ashlyn™ Bath Collection creates a modern appeal at an attractive price.

- MultiChoice® Universal makes it easy to upgrade a shower without altering the plumbing behind the wall.
- Use the In2ition® Shower like a showerhead, or simply remove the handshower to rinse from a close range.
- Water-efficient faucets and showers—Delta Faucet Company is the EPA's 2011 and 2013 WaterSense® Manufacturer Partner of the Year.
- EZ Anchor® simplifies installation with above deck mounting.
- The Ashlyn™ Bath Collection features a full suite of products.



Single-Hole
564-MPU-DST
Optional escutcheon included



Two Handle Center Set
2564-MPU-DST



Two Handle Centerset Lav Faucet -
Tract Pack
2564-TP-DST



EZ Anchor® —
Simplifies installation by
allowing the faucet to be
secured from above the sink
without having to go under
the sink to tighten it.



Two Handle Widespread
3564-MPU-DST



3-Hole Roman Tub
T2764
R2707 (not shown)



4-Hole Roman Tub
T4764
R4707 (not shown)



DIAMOND™ Seal Technology—
A tough, diamond-embedded
ceramic valve lasts up to five
million uses.



ASHLYN™ BATH COLLECTION



Monitor® 14 Series
Tub & Shower
T14464
R10000-UNBX (not shown)



Monitor 17 Series Shower Only
T17264
R10000-UNBX (not shown)



In2ition® Two-in-One Shower
58064




Monitor 17 Series
Shower with In2ition®
T17464-I
R10000-UNBX



TouchClean® soft rubber spray holes allow you to easily wipe away calcium and lime build-up from the spray face with the touch of a finger.



76418 18" Towel Bar
76424 24" Towel Bar
76435 Double Robe Hook
76446 Towel Ring
46450 Tissue Holder



All products are shown in Chrome unless otherwise noted.



see what Delta can do™

deltafaucet.com
800.345.DELTA (3358)
©2014 Masco Corporation of Indiana
DL-1852 08/14

= DIAMOND™ Seal Technology

= WaterSense® Labeled Product—
Lavatory Faucets: flow rate of 1.5 gpm versus Industry Standard ASME A112.18.1/CSA B125.1 of 2.2 gpm and meet CALGreen standards.

Showerheads: flow rate of 1.5 gpm or 2.0 gpm versus Industry Standard ASME A112.18.1/CSA B125.1 of 2.5 gpm and meet CALGreen standards.

= Compliant with State and Federal drinking water legislation.

= EZ Anchor simplifies installation by allowing the faucet to be secured from above the sink without having to go under the sink to tighten it.

WaterSense is a registered trademark of the U.S. Environmental Protection Agency.

= Pause

= Full Body Spray

= Full Spray with Massage

= Fast Massage

= Slow Massage

= High Efficiency