

TOTO®

# ECOPOWER® FAUCETS

0.35 GPM FLOW RATE



# LEAD WITH **SUSTAINABLE SOLUTIONS**

TOTO's line of high-efficiency commercial bathroom products use natural resources responsibly and contribute to earning LEED® credits. Our eco-friendly technology helps you save water, energy and money without sacrificing performance.



# ECOPOWER® 0.35 GPM FAUCET FEATURES



AXIOM® FAUCET  
TEL143



HELIX® FAUCET  
TEL113



HELIX M FAUCET  
TEL123



EcoPower



Auto  
Functions



ADA



HELIX WALL-MOUNT  
FAUCET  
TEL133



STANDARD FAUCET  
TEL103

## PRODUCT FUNCTIONS

- » Self-generating hydropower EcoPower system
- » 0.35 GPM aerated flow
- » Contributes to earning LEED credits
- » No minimum daily usage requirement
- » Microsensor positioned underneath the spout head for accurate hand detection ensuring smooth and consistent water distribution
- » Durable chrome plated spout body
- » Single-hole mount
- » Kit includes spout body, controller box , and mounting hardware - less supply lines

## PRODUCT SPECIFICATIONS

|                              |  |                 |
|------------------------------|--|-----------------|
| <b>Power Supply</b>          | EcoPower   |                 |
| <b>Sensor Range</b>          | 5-1/8" - 7-7/8" (130 - 200mm)<br>Self-Adjusting Sensor   |                 |
| <b>Water Supply</b>          | G1/2 (1/2 NPSM Compatible)   |                 |
| <b>Water Supply Pressure</b> | <b>Min. Pressure (Dynamic/Flowing)</b>   | 15 psi (100kPa) |
|                              | <b>Max Pressure (Static)</b>   | 80 psi (551kPa) |
| <b>Inlet Temp. Range</b>     | 32-110°F (0-42°C)  |                 |
| <b>Ambient Temp.</b>         | 32-104°F (0-40°C)  |                 |
| <b>Humidity</b>              | Max 90% RH   |                 |
| <b>Flow Rate</b>             | 0.11 GPC* - Max 20 Sec On-Demand**<br>(0.11 GPC = 0.35 GPM x 20/60 Sec)<br>Equipped with 0.35 GPM Flow Control |                 |
| <b>Warranty</b>              | Three Years  |                 |

\*Gallons per cycle (GPC) is the amount of water per usage cycle.  
\*\*On-demand refers to the way in which the water is dispersed (i.e.; water is only dispersed when the sensor is activated by the user as needed).



**TOTO USA, INC.**  
1155 SOUTHERN ROAD  
MORROW, GA 30260  
800-350-8686

[www.totousa.com](http://www.totousa.com)