




DCE33 - 30 lb Gourmet Ice Machine

Under-Counter Gourmet Ice Machine



Features

- 15" cabinet width, produces up to 30 lbs. of gourmet ice in 24 hours. Stores up to 26 lbs.
- Uniquely-shaped, crystal-clear, slow-melting, taste-free, odorless ice - won't dilute the flavor of drinks.
- Maintains ideal bin capacity with automatic shut-off and restart.
- Accepts custom wood panels to match you decor.
- Available with built-in drain pump.
- Perfect match with Scotsman Refrigerator and Wine Storage Unit.
- Available in black finish only.

24 Hour Ice Production & Storage Capacity

70°F/21°C Air 50°F/10°C Water lb / kg	90°F/32°C Air 70°F/21°C Water lb / kg	Bin Storage Capacity lb / kg
30 / 13.6	16 / 7.2	26 / 12



Gourmet Ice




Gourmet Cube
1" x 1 1/8" x 1 1/4"
(2.54 x 2.86 x 3.18 cm)

Large, slow-melting ice form, ideal for mixed drinks.

Warranty

- 1 years parts and labor on all components.
- 5 years parts on the compressor only.

Warranty valid in North America.



All Models

24 Hour Ice Production:
 (70 deg. Air/50 deg. Water)
 30 lb / 13.6 kg
 (90 deg. Air / 70 Deg. Water)
 16 lb / 7.2 kg

Bin Storage Capacity:
 26 lb / 12 kg

Condenser Type:
 Air

Basic Electrical:
 (Volts/Hz/Phase)
 115/60/1

Amps:
 3.6

Maximum Fuze Size:
 15

Refrigerant:
 R-134A

Dimensions (W x D x H):
 Unit (without legs):
 15" x 22.8125" x 33.875"
 (38.1 x 57.94 x 86.04 cm)

Shipping Carton:
 18" x 28" x 38"
 (45.7 x 71.1 x 96.5 cm)

Specifications

Model	Finish Cabinet / Front	Drain Type	Shipping Weight lb / kg
DCE33A-1BC	Black / Black	Gravity	88 / 40
DCE33PA-1BC	Black / Black	Pump	88 / 40

DCE33A: Gravity flow drain tube
 DCE33PA: Built-in pump to expel drain water which includes 10' drain tube

Accessories

Model	Description	Shipping Weight lb / kg
SS-33	Stainless Steel Front Panel Kit	9 / 4
KHAND	Custom Handle Trim Piece (Top)	1 / 0.45
KCE18	18" Filler Kit - Available in Black Only	5 / 2.3
KD Black	Handle with Black Label for DCE	1 / 0.45
KSS	Wrap Around Stainless Steel Door Sleeve Kit	12 / 5.5

Operating Requirements

	Minimum	Maximum
Air Temperatures	50°F (10°C)	100°F (38°C)
Water Temperatures	40°F (4.4°C)	100°F (38°C)
Water Pressures	14 PSIG (1 bar)	70 PSIG (5 bar)
Electrical Voltage	-10%	+10%

Machine requires voltage indicated on rating name plate. Failures caused by improper voltage are not considered factory defects. Scotsman products, except model SCCG50MA-1SS & SCCP5050MA-1SS, are not designed for outdoor installations nor for installation where air temperatures fall below 50°F. or exceed 100°F., nor where water temperatures fall below 40°F. or exceed 100°F. Extended periods of operation at temperatures exceeding these limitations constitute misuse under the terms of Scotsman Manufacturer's Limited Warranty, resulting in a loss of warranty coverage. Refer to owner's manual for all installation requirements. Please note: when installed in a corner, the door swing may be limited due to handle contact with the wall or cabinet face.